


## DDR4

The Global Leader in Specialized Storage and Memory Solutions



## **KEY FEATURES**

- Density: 2 GB to 128 GB
- Increased performance and bandwidth (up to 3200 MT/s)
- Decreased voltage for better power consumption
- Provides better reliability, availability and serviceability (RAS) and improves data integrity

ATP's fourth-generation industrial DDR memory combines up to 3200 MT/s data transfer rate and a mere 1.2V power consumption to deliver faster performance at higher power savings over earlier DRAM technologies.

As the evolutionary transition from DDR3, DDR4 supports features and functions that are well-suited for increasing bandwidth capabilities to support the growth of online traffic.

DDR4-3200 MT/s is the newest generation of fast, performance-oriented DRAM modules optimized for the latest Intel® Xeon® Platinum, Gold, Silver and Bronze Scalable processors and 8th-generation Intel® Core™ i7/i5/i3 processors. The increased interface speed from 2400 MT/s to 3200 MT/s amplifies theoretical peak performance by 20% and gives a boost to the most critical computing applications in industries such as telecommunication infrastructures, networking storage systems, network-attached storage (NAS) servers, micro/cloud servers, and embedded systems like industrial PCs.

Technol Add-On S					Anti-Sulfur Resistors	Conformal Coating	
RDII	ИM	•	•	<b>A</b>	<b>A</b>	_	<b>A</b>
ECC UI	MMIC	•	•	<b>A</b>	<b>A</b>	<b>A</b>	<b>A</b>
Non-ECC	Non-ECC UDIMM		•	<b>A</b>	<b>A</b>	<b>A</b>	<b>A</b>
ECC SO-	DIMM	•	•	<b>A</b>	<b>A</b>	<b>A</b>	<b>A</b>
Non-ECC S	O-DIMM	•	•	<b>A</b>	<b>A</b>	<b>A</b>	<b>A</b>
Mini-R	DIMM	•	•	<b>A</b>	<b>A</b>	_	-
Mini-U	DIMM	•	•	<b>A</b>	<b>A</b>	_	_

▲: Optional

## **Specifications**

DDR4										
DIMM Type	RDIMM	ECC UDIMM	Non-ECC UDIMM		Non-ECC SO-DIMM	Mini-RDIMM	Mini-UDIMM			
Density	4 GB to 128 GB	4 GB to 32 GB	2 GB to 32 GB	4 GB to 32 GB	2 GB to 32 GB	4 GB to 16 GB	4 GB to 16 GB			
Speed up to (MT/s)			2400							
PCB Height*	Low profile / VLP / ULP			Low profile		Low profile / VLP	VLP			
Operating Temperature	0°C to 85°C / -40°C to 85°C									

<sup>\*</sup> VLP: 0.74", ULP: below 0.74"



The Global Leader in Specialized Storage and Memory Solutions

## **WE BUILD WITH YOU**

Please refer to www.atpinc.com for latest information

Product spec and its related information are subject to change without

v1 022024

advance notice.

© Copyright 2024 ATP Electronics, Inc. All rights reserved.

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368 sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000

sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0 sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797 sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220 sales@cn.atpinc.com