




# USB 2.0 eUSB

The Global Leader in Specialized Storage and Memory Solutions



## KEY FEATURES

- Superior Random Write Performance
- Global wear leveling
- Power Loss Protection
- Hardware Write Protect\*

\* May vary by product and project support

The ATP eUSB module employs the widely supported USB interface, making it a suitable boot device and efficient data storage solution.

Ideal for industrial and rugged environments, the eUSB module is cost-effective and offers data transfer efficiency in a wide range of applications such as networking, embedded and medical applications that previously used the Intel® Z-U130 Value SSD.

With Power Loss Protection technology options featuring built-in hardware-based power backup circuit and/or firmware-based solution, ATP eUSB delivers reliable controller and lasting NAND flash operation even during sudden power-loss events.

Technologies		S.M.A.R.T/ Life Monitor	Industrial Temperature	Firmware-Based Power Loss Protection	Hardware-Based Power Loss Protection	Advanced Wear Leveling	Hardware Write Protect
Premium	B800Pi	○	○	○	▲	○	▲
Superior	B600Sc	○		○	○	○	

▲: Customization option available on a project basis.

## Specifications

Product Line	Premium		Superior
	B800Pi	B800Pi	B600Sc
Interface	USB 2.0 (480 Mbps)		
Flash Type	SLC		MLC
Form Factor	Pitch 2.54 mm / 2.00 mm		
Operating Temperature	-40°C to 85°C		0°C to 70°C
Power Loss Protection Options	Firmware Based	Hardware + Firmware Based	
Optional SED Features	-		
Capacity	1 GB to 16 GB	1 GB to 32 GB	8 GB to 32 GB
Performance			
Sequential Read (MB/s) up to	37	30	25
Sequential Write (MB/s) up to	23	25	19
Endurance and Reliability			
Endurance (TBW) <sup>1</sup> up to	1,548 TB	640 TB	19 TB <sup>2</sup>
Reliability MTBF @ 25°C	>5,000,000 hours		>2,000,000 hours
Reliability Number of Insertions	10,000 minimum		
Others			
Dimensions (mm)	36.9 x 26.6 x 9.5		
Certifications	CE, FCC, UKCA, RoHS		
Warranty	5 years		2 years

1. Under highest Sequential write value. May vary by density, configuration and applications.
2. Measured with Random Write. May vary by density, configuration and applications.



The Global Leader in Specialized Storage and Memory Solutions

# WE BUILD WITH YOU

Product spec and its related information are subject to change without advance notice.

Please refer to [www.atpinc.com](http://www.atpinc.com) for latest information

v1.0 012025

© Copyright 2025 ATP Electronics, Inc. All rights reserved.

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368  
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000  
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0  
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797  
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220  
sales@cn.atpinc.com

ATP INDIA

sales-india@atpinc.com